

Click! | Technical specification



MEASUREMENTS

	CLICK! FLEXI	CLICK! LIGHT	CLICK! EX	CLICK! SAFETY+
CH4	Yes	Yes	Yes	Yes
CO2	Yes	Yes	Yes	-
H2S	Yes	Yes	Yes	Yes
O2	Yes	Yes	Yes	-
CO	Yes	Yes	Yes	-
H2	Yes	Yes	Yes	-

ENVIRONMENTAL CONDITIONS

	CLICK! FLEXI	CLICK! LIGHT	CLICK! EX	CLICK! SAFETY+
Operating temperature	-10°C to +40°C	+10°C to +40°C	+10°C to +40°C	+10°C to +40°C
Ingress protection	IP56	IP56	IP56	IP56
Maximum input pressure	30mb	30mb	30mb	30mb

GENERAL

	CLICK! FLEXI	CLICK! LIGHT	CLICK! EX	CLICK! SAFETY+
Supply input	24VDC, 110-240VAC	24VDC, 110-240VAC	24VDC, 110-240VAC	24VDC, 110-240VAC
Material	GRP	GRP	Aluminium	GRP
Additional sample points	Up to 10	-	-	-
Default data output	SD card	SD card	SD card	SD card
Display	Inner door display	-	Optional control panel	HMI touch screen
ATEX certification	-	-	II 2 G Ex db IIB T6 Gb	-