

Inspectra MAX |

Technical specification



MEASUREMENTS

SENSOR	TYPE	UNITS	RANGE	DETECTION THRESHOLD	RESPONSE TIME (T90)	PUMP FLOW RATE
CH4	Laser	ppm % gas volume % LEL (optional)	0-100% gas volume	0.5ppm	4.5s 6s (with suction rod)	30l/h (slow speed) 70l/h (high speed)

FACILITIES

Display	LCD screen with backlight 60° viewing angle Contracts constant from -15°C to +50°C / +5°F to +122°F
Keypad	5 direct control keys Protected-access scrolling menu
Start-up time	<15s
Concentration display	Continuous reading display
Alarms	Visual and audio Concentration threshold Pump stop / pump error
Status indicators	Battery charge level Pump status

POWER SUPPLY

Battery type	NiMH rechargeable battery pack: 3 x 1.2V-6450mAh
Battery life	12 hours at 20°C to 25°C / 68°F to 77°F
Battery charger	100-240VAC 50Hz-60Hz
Charge time	10 hours at 1Ah

ENVIRONMENTAL CONDITIONS

Operating temperature	-15°C to +50°C / +5°F to 122°F
Atmospheric pressure	1013mbar (+/- 100mbar)
Humidity	5 to 80% relative humidity

Inspectra MAX |

Technical specification



PHYSICAL

Gas connection	Quick-connect inlet coupling with locking mechanism Quick-connect gas outlet coupling
Electrical connection	Male power plug 2.1mm for battery charger External bluetooth connector (optional)
Dimensions	263mm x 113mm x 141mm 10.3" x 4.4" x 5.5"
Weight	2.7kg / 5.95lbs with batteries
Protection rating	IP54

CERTIFICATION RATING

Standard conformity	CE Marking EN 61010 :2010 + A1:2019/AC 2019-04 Safety requirements for electrical equipment for measurement, control and laboratory use EN 50270 :2015 Electromagnetic compatibility
ATEX Zone 1	Ex II 2 G Ex ib op is IIB T3 Gb INERIS 19ATEX0018X
IECEX	II2G Ex ib op is IIB T3 Gb IECEX INE 19.0017X

DATA & COMMUNICATIONS

Connection	Bluetooth communication with mobile devices (optional)
Data recording	Data transfer to GAZOMAT app (optional)